

# Клеммные коробки из нержавеющей стали ELDON ZONEX EXE-SB, EXE-NB

## Технические характеристики



Архангельск (8182)63-90-72  
Астана (7172)727-132  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89  
Иваново (4932)77-34-06

Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижегород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16

Россия (495)268-04-70

Пермь (342)205-81-47  
Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13

Казахстан (772)734-952-31

Сургут (3462)77-98-35  
Тверь (4822)63-31-35  
Томск (3822)98-41-53  
Тула (4872)74-02-29  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Ярославль (4852)69-52-93

# Terminal Boxes

## Hazardous Location Range

### ZONEX, Stainless Steel Terminal Box, EXE-SB

- Material:** Fabricated from Type 316L stainless steel. Body: 1.5 mm. Cover: 1.5 mm. Mounting plate: 2.0 mm galvanized steel.
- Body:** M6 brass internal/external bonding provision. Full-width welded wall-mounting brackets on top and bottom. Internal weld studs for panel or DIN rail mounting brackets.
- Cover:** M6 brass internal/external bonding provision. Full-width welded wall-mounting brackets on top and bottom. Internal weld studs for panel or DIN rail mounting brackets.
- Protection:** IP 66 | TYPE 4, 4X, 12
- Finish:** 320 grain brushed finish.
- Approvals:**
- |                               |                       |
|-------------------------------|-----------------------|
| <b>ATEX Directive 94/9/EC</b> | <b>IECEX</b>          |
| Sira 09ATEX3224U              | IECEX SIR 09.0099U    |
| Ex eb IIC Gb                  | Ex eb IIC Gb          |
| Ex tb IIIC Db IP 66           | Ex tb IIIC Db IP 66   |
| EN60079-0:2009                | IEC 60079-0:2007-2010 |
| EN60079-7:2007                | IEC 60079-7:2006-2007 |
| EN61241-0:2006                | IEC 61241-0:2004      |
| EN61241-1:2004                | IEC 61241-1:2004      |
- Delivery:** Enclosure with cover, cover screws, mounting plate and mounting accessories.
- Note:** nVent HOFFMAN ATEX Ex e enclosures are not intended for use in explosion-proof or flame-proof applications.



H	W	D	Mounting Plate Height	Mounting Plate Width	Item no.
102	102	76	84,8	84,8	EXE101008SS6E
152	152	102	134,8	134,8	EXE151510SS6E
178	178	102	160,8	160,8	EXE181810SS6E
216	146	127	198,8	128,8	EXE221513SS6E
254	254	127	236,8	236,8	EXE252513SS6E

# Terminal Boxes

## Hazardous Location Range

### ZONEX, Polyester Terminal Box, EXE-NB

<b>Description:</b>	Polyester terminal box for increased safety Ex e applications. Compression-moulded glass fibre reinforced polyester with added agents to address static charge build-up. Internal M4 or M6 stainless steel inserts for DIN- and panel-mounting. Mounting location dimensions are moulded into the back side of the enclosure. Covered mounting screw provisions outside of gasketed area.	
<b>Material:</b>	Body and cover: Compression-moulded, high-impact strength, glass fibre reinforced polyester. Screws: Stainless steel.	
<b>Gasket:</b>	Retained, continuous, high-temperature silicone gasket within a labyrinth seal between cover and body.	
<b>Operating temperature:</b>	-50 to +100 °C	
<b>Flammability:</b>	UL 94 V-0.	
<b>Protection:</b>	IP 66   TYPE 4, 4X, 12	
<b>Finish:</b>	Moulded material has a smooth, low-gloss, black finish RAL 9005.	
<b>Approvals:</b>	<b>ATEX DIRECTIVE 94/9/EC</b> ATEX TUV 13 ATEX120808U Ex eb IIC Gb Ex tb IIIC Db IP 66 EN60079-0 EN60079-7 EN60079-31 Service temperature -50 to +100 °C	<b>IECEX</b> IECEX TUV 13.0001U Ex eb IIC Gb Ex tb IIIC Db IP 66 IEC 60079-0 IEC 60079-7 IEC 60079-31 Service temperature -50 to +100 °C
<b>Delivery:</b>	Body, door and cover screws.	
<b>Note:</b>	This is not an explosion-proof enclosure. Mounting plate available separately.	



H	W	D	Item no.
75	80	55	EXE807555
75	80	75	EXE807575
75	110	55	EXE1107555
75	110	75	EXE1107575
75	160	55	EXE1607555
75	160	75	EXE1607575
75	190	55	EXE1907555
75	190	75	EXE1907575
120	122	90	EXE12212090
120	220	90	EXE22012090
160	160	90	EXE16016090
160	260	90	EXE26016090
160	360	90	EXE36016090
160	560	90	EXE56016090
250	255	120	EXE255250120
250	400	120	EXE400250120
405	400	120	EXE400405120

