

Аксессуары: освещение и розетки

Светодиодные подсветки корпуса с разъемом, датчиком движения ELDON EL1200M, EL900DS, EL900D, EL1200M24V

Технические характеристики



Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Россия (495)268-04-70

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Казахстан (772)734-952-31

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

General Accessories

Lighting & Sockets

LED Enclosure light with movement sensor, EL1200M

Description:	LED enclosure light specially designed for nVent HOFFMAN enclosures. Fast and tool-free assembly thanks to a latching hook system designed to fit the 25mm hole pattern on nVent HOFFMAN enclosures. May be fitted horizontally or vertically.
Lamp type:	LED.
Luminosity:	1200 lm.
Light colour:	4000 K (neutral white).
Power consumption:	12 W
Operating voltage:	100 V - 240 V ~, 50/60 Hz
Connection:	Infeed, 3-pole. Through wiring, 3-pole.
Operating temperature:	-20 °C ... +55 °C
Protection:	IP20
Follow-up time of the motion detector:	120 s
Dimensions:	315 x 76 x 48 mm.

Operating voltage	Width	Item no.
100 V - 240 V ~, 50/60 Hz	315	EL1200M



LED Enclosure light with socket, EL900DS

Description:	LED enclosure light specially designed for nVent HOFFMAN enclosures. Fast and tool-free assembly thanks to a latching hook system designed to fit the 25mm hole pattern on nVent HOFFMAN enclosures. May be fitted horizontally or vertically.
Lamp type:	LED.
Luminosity:	900 lm.
Light colour:	4000 K (neutral white).
Power consumption:	9 W
Operating voltage:	100 V - 240 V ~, 50/60 Hz
Connection:	Infeed, 3-pole. Through wiring, 3-pole.
Operating temperature:	-20 °C ... +55 °C
Protection:	IP20
Dimensions:	364 x 76 x 48

Operating voltage	Socket type	Width	Item no.
100 V - 240 V ~, 50/60 Hz	Type F (Shucko)	364	EL900DS
100 V - 240 V ~, 50/60 Hz	Type E	364	EL900DS-BF
100 V - 240 V ~, 50/60 Hz	Type J	364	EL900DS-CH
100 V - 240 V ~, 50/60 Hz	Type G	364	EL900DS-GB
100 V - 240 V ~, 50/60 Hz	Type B	364	EL900DS-US



LED Enclosure light, EL900D

Description:	LED enclosure light specially designed for nVent HOFFMAN enclosures. Fast and tool-free assembly thanks to a latching hook system designed to fit the 25mm hole pattern on nVent HOFFMAN enclosures. May be fitted horizontally or vertically.
Lamp type:	LED.
Luminosity:	900 lm.
Light colour:	4000 K (neutral white).
Power consumption:	9 W.
Operating voltage:	100 V - 240 V ~, 50/60 Hz.
Connection:	Infeed, 3-pole. Through wiring, 3-pole.
Operating temperature:	-20 °C ... +55 °C.
Protection:	IP20
Dimensions:	314 × 76 × 48 mm.

Operating voltage	Width	Item no.
100 V - 240 V ~, 50/60 Hz	314	EL900D



LED Enclosure light 24V with movement sensor, EL1200M24V

Description:	LED enclosure light specially designed for nVent HOFFMAN enclosures. Fast and tool-free assembly thanks to a latching hook system designed to fit the 25mm hole pattern on nVent HOFFMAN enclosures. May be fitted horizontally or vertically.
Lamp type:	LED.
Luminosity:	1200 lm.
Light colour:	4000 K (neutral white).
Power consumption:	12 W
Operating voltage:	24 V DC
Connection:	Infeed, 2-pole. Through wiring, 2-pole.
Operating temperature:	-20 °C ... +55 °C
Protection:	IP20
Follow-up time of the motion detector:	120 s
Dimensions:	314 × 76 × 48

Operating voltage	Width	Item no.
24 V DC	314	EL1200M24V



Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Россия (495)268-04-70

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Казахстан (772)734-952-31

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93